

# RP076X-NR ZIPSPEED TROLLEYS

Product Data Sheet

123456789  
345678912  
567891234  
789123456  
912345678



## PRODUCT OVERVIEW

The ZipSpeed-L Noise Reduction Trolley is fitted with special Nylon Wheels, to reduce sound output by ~7dB. Zip builders/operators are under increasing pressure to take a pro-active approach to reducing the noise generated from zip lines. The ability to minimise noise in consideration of the effect on local residents and wildlife, plays a pivotal role for operators who are seeking local authority planning permission, for installation of zip lines at their sites.

Noise Reduction Wheels are available on our 13mm and 16mm (1/2" and 5/8") ZipSpeed models. ZipSpeed Noise Reduction Trolleys are suitable for use on industry-standard Zipline cables, however for maximum performance and durability, we recommend the use of smooth-surfaced 'Interlocked' cable.

## TECHNICAL INFORMATION

Part Codes	RP076A-NR 13mm (1/2") RP076B-NR 16mm (5/8")
Weight	1kg (2.2lb)
Length	287mm (11 <sup>19</sup> / <sub>64</sub> "
Height	142mm (5 <sup>19</sup> / <sub>32</sub> "
Width	32mm (1 <sup>7</sup> / <sub>64</sub> "
Wheel Type	Ø80mm (3 <sup>5</sup> / <sub>32</sub> "), Bearing
Wheel Material	Nylon
Body Material	Aluminium
MBS	40kN (8992lbf)
Central Axles	RP076A-NR 13mm (1/2"), Grey RP076B-NR 16mm (5/8"), Orange