

RINXXX SATURN SERIES RIGGING RING

Product Datasheet

123456
34567
56789



RIN4452 Large

RIN3238 Medium

RIN2528 Small



RIN2528 Small

Made in Wales, UK

PRODUCT OVERVIEW

SATURN Series Rigging Rings are CNC Machined from solid Aluminium, with smooth radiused rope surfaces. The rings have a Hard-Anodised coating for durability and a polished, low-friction finish. ISC SATURN Rigging Rings are available in three sizes and can be used in a wide variety of rigging configurations. SATURN Rings can also be spliced in to anchor slings by the supplier/user and used to create single/multiple redirects, to tailor the friction in a rigging system. Rigging rings are versatile, low maintenance and easy to inspect.

TECHNICAL INFORMATION

Part Code	RIN2528 Small	RIN3238 Medium	RIN4452 Large
Overall Diameter	88mm (3.5")	112mm (4.4oz)	138mm (5.4")
Inner Diameter	28mm (1.1")	38mm (1.5")	52mm (2")
Groove Radius (Rope path)	25mm (0.98")	32mm (1.25")	44mm (1.73")
MBS	140kN (31473lbf)	200kN (44961lbf)	300kN (67442lbf)
WLL	28kN (6294lbf)	40kN (8992lbf)	60kN (13488lbf)
Weight	302g (10.6oz)	591g (20.8oz)	1073g (37.8oz)
Material/finish	Aluminium/ Polished & Hard Anodised		
Standards	CE 2006/42/EC UKCA		